

## Stuffing Box Packing

### Style Aidmer76-028 PTFE Asbestos Packing



**Material:**

Square braided white and long asbestos fiber cords impregnated with PTFE emulsion.(addition of lubricant is optional.)

**Application Areas:**

Style Aidmer76-028 can be used in all rotating and reciprocating pumps, mixers and valves.

**Application Media:**

Style Aidmer76-028 is suitable for sealing against hot and cold water, ammonia, caustics, mild acids, difficult chemicals, air, gases, steam, solvents, oil and most marine applications.

**Application Data:**

	Rotary	Reciprocating	Valve
Pressure:bar	50	100	150
Speed:m/s	10	3	1.5
pH Range	2 - 12		
Temp. °C	Max.+260		

**Stock Dimension:** (Max. size: 4" square)

mm sq.	3	4	5	6	7	8	10	11	12	13	14	15	16	18	19	20	22	24	25	
M/kg.abt.	74	41	27	19	14	11.1	7.0	6.0	5.0	4.2	3.75	3.3	3.0	2.35	2.13	1.95	1.65	1.43	1.31	
Inch sq	1/8	5/32	3/16	1/4		5/16	3/8	7/16	1/2		9/16		5/8	11/16	3/4	13/16	7/8	15/16	1	
Ft/Lb.abt	96	64	43	25		16.3	11.6	8.6	6.95		5.40		4.50	3.75	3.15	2.80	2.40	2.10	1.85	
Packagin g	1kgs per coil				2.5kgs per coil					5kgs per coil										

(Other Packaging on your request)